

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

<IDS>

INPADOC문서보기	원문보기 번역문보기
EXPANSION VALVE	

(19) 국가 (Country) : JP (Japan)

(11) 공개번호 (Publication Number) : 2001-241808 (2001.09.07)

(13) 문헌종류 (Kind of Document) : A (Unexamined Publication)

(72) 발명자 (Inventor) : FUKUDA EIJI, WATANABE KAZUHIKO

(71) 출원인 (Applicant) : FUJI KOKI CORP

(57) 요약 (Abstract) :

PROBLEM TO BE SOLVED: To improve a degree of freedom in a fixing structure of an expansion valve used in a freazing cycle of an automobile air conditioner.

SOLUTION: An expansion valve 1 has a main body 10 of rectangular column shape and a valve chamber 20 is formed within the main body 10. Refrigerant supplied from a compressor flows from a passage 22 into a valve chamber, passes between a valve member 42 and a valve seat 22, and flows from a passage 24 toward an evaporator. The refrigerant returned from the evaporator enters from a passage 26 into the main body 10 and, after the refrigerant transmits temperature information of refrigerant against an operating rod 40, the refrigerant flows from a passage 28 to the compressor. The passage 22 and the passage 28 are opened at the first side surface of the main body and the passages 24, 26 are opened at a side surface perpendicular to the first side surface. With such an arrangement as above, a degree of freedom of the fixing structure of the expansion valve 1 is improved.

COPYRIGHT: (C)2001,JPO

2000-056755 (2000.03.02)

F25B-041/06 : B60H-001/32 : F16K-031/68

(21) 출원번호 (Application Number)

(54) 국제특허분류 (IPC)

2/3

F253-041/06 F
B60H-001/32 613 B
F16K-031/68 S

3H057

3H057: AA04 BB49 CC06 CC11 DD01 EE03 FA24 FC05 HH05 HH18 HH20

(30) 우선권번호 (Priority Number):

본 특허를 우선권으로 한 특허:

EP 1130345 A1 (2001.09.05)
KR 2001-0087213 A (2001.09.15)
US 6434971 B1 (2002.08.20)
US 20010018830 A1 (2001.09.06)

대표도면:

